

## **EXTREME GEARED REEL**

*Rugged, reliable and built for performance, the Speedrite Extreme Geared Reel reimagines everything you thought you knew about electric fence reels.*



**REIMAGINE SIMPLICITY WITH SMOOTH TANGLE-FREE WIRE AND POLITAPE SPOOLING**

**REIMAGINE CONNECTION WITH QUICK LOCKING AND SEAMLESS ELECTRIFICATION**

**REIMAGINE EFFICIENCY WITH RAPID RETURN 3:1 GEARING**

### **BUILT FOR YOU**

You want a reel that saves you time, saves you hassle and that goes where you need it to go.

Our new Extreme Geared Reel is easy to use, operates smoothly and is rugged enough to hook on anywhere you need it to without coming free.

### **ENGINEERED FOR PERFORMANCE**

Our engineering team has redesigned our reel from scratch, breaking down its essential functions and reimagining how to deliver the best performance for you.

- ✓ *HOLDS 500 M OF POLIWIRE OR 200 M OF 12 MM POLITAPE*
- ✓ *3:1 GEAR RATIO WITH A SOLID STEEL CRANK*
- ✓ *WIRE TRACKING FOR EVEN WIRE DISTRIBUTION ACROSS THE BOBBIN*
- ✓ *DRAG ADJUSTMENT TO PREVENT OVER RUN AND TANGLING*
- ✓ *ISOLATED POWER FLOW THROUGH THE REEL FRAME*
- ✓ *ON/OFF POWER SWITCH FOR FINGERTIP CONTROL*
- ✓ *NEW HOOK DESIGN FOR ENHANCED STABILITY ON FENCE OR BIKE*
- ✓ *HOOK FITS A RANGE OF BAR WIDTHS*
- ✓ *FRAME INSULATED FROM SPOOL*
- ✓ *UV STABILISED MATERIALS FOR LONG LIFE AND DURABILITY*
- ✓ *2 YEAR WARRANTY*

## SPECIFICATIONS

<b>PRODUCT CODES</b>	<b>880 0004-621</b> REEL SPE EXTREME GEARED W/ZAMMR
	<b>880 0004-625</b> REEL SPE EXTREME GEARED+EXTWIRE 400M W/ZAMMR WHI
	<b>880 0004-627</b> REEL SPE EXTREME GEARED+PTAPE S8 200M W/ZAMMR WHI
	<b>880 0004-631</b> REEL SPE EXTREME GEARED+PWIRE 6SS 500M W/ZAMMR WHI
	<b>880 0004-633</b> REEL SPE EXTREME GEARED+EXTTAPE 200M W/ZAMMR WHI

<b>HEIGHT</b>	340 mm
<b>LENGTH</b>	360 mm
<b>WIDTH</b>	360 mm

<b>WEIGHT (SPOOL EMPTY)</b>	2.2Kg
-----------------------------	-------

<b>MAX SPOOL CAPACITY POLIWIRE, POLITAPE, EXT WIRE, EXT TAPE</b>	500m
--	------

<b>SHIPPING</b>	Four units per carton
-----------------	-----------------------

<b>LOCKING HOOK MAX BAR DIAMETER MIN BAR DIAMETER</b>	30mm 18mm
---	--------------

<b>WIRE LOCK MAX WIRE DIAMETER MIN WIRE DIAMETER</b>	4mm 2.5mm
--	--------------

<b>DRAG FORCE</b>	2Kg +0.5 -0
-------------------	-------------

<b>GEAR RATIO</b>	3:1
-------------------	-----

<b>WINDING TORQUE (EMPTY SPOOL)</b>	< 70 mNm
---	----------

<b>HOOK TO POLIWIRE/ POLITAPE RESISTANCE</b>	<= 6 Ohm
--	----------

<b>OPERATIONAL TEMPERATURE RANGE</b>	-5 to +50 DegC
--	----------------

## SPARE PARTS

<b>880 0004-681</b> Spare Bobbin Generic	<b>880 0004-685</b> Spare Rotary Switch	<b>880 0004-689</b> Spare Crank Handle Outer	<b>880 0004-693</b> Spare Traveller Kit
<b>880 0004-682</b> Spare Gearbox Yellow	<b>880 0004-686</b> Spare Drag Spring	<b>880 0004-690</b> Spare Crankshaft Kit	<b>880 0004-694</b> Spare Trigger Spring
<b>880 0004-683</b> Spare Wool Washer	<b>880 0004-687</b> Spare Aluminium Rolling Bar	<b>880 0004-691</b> Spare Drive Belt	<b>880 0004-696</b> Spare Cover Kit SPE
<b>880 0004-684</b> Spare Handle Kit	<b>880 0004-688</b> Spare Crank Handle Inner	<b>880 0004-692</b> Spare Worm Shaft Kit	

Although the information presented in this Product Information Sheet is believed to be accurate and reliable, no responsibility for inaccuracies can be assumed by Datamars. Performance data is typical only and variations due to component manufacturing tolerances are normal. Datamars reserves the right at any time to change performance characteristics or specifications without prior notice.

© Datamars – All rights reserved.

4009SPE14 SPE PREMIUM GEARED REEL DATASHEET ISSUE 1 03/22